

TTP POLSKA Sp. z o.o.

ul. Długa 25 43-365 Wilkowice tel/fax: 33 816 04 14 e-mail: biuro@ttppolska.pl



## POWER F-LUBE

**FLB** 



NSF H1 registration compatible product Content compatible with FDA regulations, section 21 CFR 178.3570

#### CAUTION

All information, including illustrations, are reliable. However, the users should evaluate the usability of each product for a given application. TTP Polska Sp. z o.o. does not guarantee the accuracy of all information and does not accept responsibility for how the products are used. The liabilities of TTP Polska Sp. z o.o. are limited solely to the standard terms and conditions of sale of the product and in no case whatsoever does TTP Polska Sp. z o.o. bear any responsibility for accidental or indirect damages resulting in the sale, use and improper use of the product.

### **GENERAL INFORMATION**

**POWER F-LUBE** is a food industry grade lubricant used also in the production of packaging for the food industry. **POWER F-LUBE** is an optimal solution for the lubrication of elements subject to large mechanical loads, extreme conditions of working environment and also for lubrication in locations with difficult or limited access. **POWER F-LUBE** may be used in a range of high temperatures without losing viscosity. **POWER F-LUBE** protects against corrosion thanks to good penetration in hard-toreach locations; also capable of establishing a thin layer of lubricating film.

#### TECHNICAL DATA

NSF H1 registration compatible product. Does not contain gluten, nuts or their derivates, or metals, animal fats and synthetic oils. Odour: odourless Thermal resistance:  $-20^{\circ}C - +200^{\circ}C$ Safety measures: provided in the safety data sheet.

#### USAGE

**POWER F-LUBE** is used in all food industry plants, and also in the production of packaging, machines, spare parts and accessories for the food industry, as well as machine maintenance and repair and devices for the food industry. **POWER F-LUBE** features high lubrication efficiency both inside and outside, and is useful in periodical lubrications even in locations with limited or difficult access.

It is first and foremost useful for work in difficult conditions, subject to constant contact with acids, alkalis, warm and cold water, vapour and high pressure.

#### CLASSIFICATION

Article code Name FLB POWER F-LUBE

Packaging BE aerosol 400 ml Type lubricants

TTP POLSKA - Top Technical Products Autonomic Group

# www.ttppolska.pl