

TTP POLSKA Sp. z o.o.

ul. Długa 25 43-365 Wilkowice tel/fax: 33 816 04 14

e-mail: biuro@ttppolska.pl



POWER PRO-ROOF

PRR10

PROBOTE POWED LONG-LASTING ELASTIC SEALANT MASS REINFORCED WITH FIBRE GLASS Sealing, adhesive bonding and repair all in one product Adheres to the majority of construction materials May be used on wet surfaces

Does not harden and retains consistent elasticity Easy and fast application with standard tools.

CAUTION

All information, including illustrations, are reliable. However, the users should evaluate the usability of each product for a given application. TTP Polska Sp. z o.o. does not guarantee the accuracy of all information and does not accept responsibility for how the products are used. The liabilities of TTP Polska Sp. z o.o. are limited solely to the standard terms and conditions of sale of the product and in no case whatsoever does TTP Polska Sp. z o.o. bear any responsibility for accidental or indirect damages resulting in the sale, use and improper use of the product.

GENERAL INFORMATION

POWER PRO-ROOF is a sealant mass of unique chemical content. It is a combination of bitumens, butyl rubber and fibre glass. The product features high stretchability and elasticity. **POWER PRO-ROOF** may be applied on the majority of construction materials, including wet surfaces.

TECHNICAL DATA

Chemical composition: modified composition of bitumens, fibre glass and butyl rubber

Stretchability: 170%

Thermal resistance: -45°C - +85°C

UV resistance: full (superb)

Aging signs: none

Water resistance: full

Carbohydrate resistance: none

Resistance to weather conditions: superb Application temperature: -10°C - +50°C

Consumption: 750 g/m² on smooth surfaces, 1.9 kg/m² on porous

surfaces

DO NOTAPPLY ON SURFACES COVERED WITH SNOW OR ICE!

USAGE

Roofing work on flat and inclined roofs connected with the repair of all types of roofings, gutters, sheet metal, etc. For safeguarding foundations, concrete structures, underground steel structures, and terraces against leaking, etc. Protection against corrosion of pipelines and underground and ground structures. As an adhesive applied cold during roof repairs with bitumen materials. **POWER PRO-ROOF** may be applied on the majority of materials used in the construction industry, e.g.: brick, concrete, ceramic materials, wood, copper, lead, galvanized steel sheets, insulation materials, PVC, polyesters and all types of materials used for roofings.

CLASSIFICATION

Article code Name Packaging Type
PRR10 POWER PRO-ROOF container 10 kg surface protection
adhesives. sealants

TTP POLSKA - Top Technical Products Autonomic Group

www.ttppolska.pl

