


PRO STRIPFIX

PRF


GENERAL INFORMATION

PRO STRIPFIX is non-solvent, synthetic, sensitive to compression, rubber-resin adhesive and sealant. It is designed for the adhesive bonding of various materials and substrates, on the condition that the adhesive bonding is established between clean, dry and non-porous surfaces. **PRO STRIPFIX** may be consistently submerged in water without any loss of adhesive and sealant properties. It should not be used in vertical assembly connections, in combination with solvents or plastic materials, and also in locations where there is a possibility of exposure to direct UV radiation. **PRO STRIPFIX** is delivered in rolls on paper substrate, wider than the adhesive film, in order to facilitate application. It may be applied directly from the roll onto dry, clean and grease-free surfaces.

TECHNICAL DATA

Stretchability: 1,000%
 Instant adhesive force (initial strength): 52 N/cm²
 Tearing strength: after 10 min. — 60 N/cm², after 24 hours — 80 N/cm²
 Consumption: 405 g/m²
 Thermal resistance: -10°C – +65°C
 Optimum application temperature: >+10°C
 Water absorbability: 0%
 Pressure needed to obtain initial adhesive strength: 1.6 kg/cm²
 UV resistance: avoid UV radiation
 Tolerance: thickness and width — +/-10%

USAGE

Adhesive bonding of prefabricated construction panes with frames. Sealing ends and side edges of profiled boards, humidity resistant membranes. Adhesive bonding of movable elements with concrete. Adhesive bonding of polyethylene boards. Fixing shower panes in place for screwing them into frames (at the same time serving as a sealant). Fixing car windows. Fixing rubber mats and linings. Fixing boards, signs, etc. Fixing furniture gussets. Fixing materials to wooden elements in window shutter rollers. Adhesive bonding of aluminium with wood. Fixing laminated frames, decorations. Fixing external roof panes of caravans.

CLASSIFICATION

Article code	Name	Packaging	Type
PRF 3012	PRO STRIPFIX 12 mm	30 m/12 mm roll	tapes
PRF 3019	PRO STRIPFIX 19 mm	30 m/19 mm roll	tapes

CAUTION

All information, including illustrations, are reliable. However, the users should evaluate the usability of each product for a given application. TTP Polska Sp. z o.o. does not guarantee the accuracy of all information and does not accept responsibility for how the products are used. The liabilities of TTP Polska Sp. z o.o. are limited solely to the standard terms and conditions of sale of the product and in no case whatsoever does TTP Polska Sp. z o.o. bear any responsibility for accidental or indirect damages resulting in the sale, use and improper use of the product.

TTP POLSKA - Top Technical Products Autonomic Group

www.tppolska.pl
