

TTP POLSKA Sp. z o.o.

ul. Długa 25 43-365 Wilkowice tel/fax: 33 816 04 14 e-mail: biuro@ttppolska.pl



PRO TOPFLUX SOLDER SHRINK

<section-header><section-header><section-header><section-header><section-header><section-header><text>

Provides perfectly waterproof connections Thermally resistant in the range of -60°C – +130°C

CAUTION

All information, including illustrations, are reliable. However, the users should evaluate the usability of each product for a given application. TTP Polska Sp. z o.o. does not guarantee the accuracy of all information and does not accept responsibility for how the products are used. The liabilities of TTP Polska Sp. z o.o. are limited solely to the standard terms and conditions of sale of the product and in no case whatsoever does TTP Polska Sp. z o.o. bear any responsibility for accidental or indirect damages resulting in the sale, use and improper use of the product.

GENERAL INFORMATION

PRO TOPFLUX SOLDER SHRINK is a heat-shrinkable polymer pipe, in which a copper spiral with an integrated soldering ring is introduced. The connector is closed with ceramic ball at one end and special adhesive sealant ring at the other end. **PRO TOPFLUX SOLDER SHRINK** has been created to establish electrical connections in locations, where reliability, water resistance and durability are all a must. **PRO TOPFLUX SOLDER SHRINK** is very easy to install, without the need for special tools, and allows the connection to be checked visually. **PRO TOPFLUX SOLDER SHRINK** is available in four sizes, indicated by a colour-coded ceramic ball. **PRO TOPFLUX SOLDER SHRINK** may be used for flexible (line) and hard (wire) electric cables (copper, galvanized and their combinations).

TECHNICAL DATA

Outer wall: heat-shrinkable polymer sleeve Soldering ring: zinc and lead ring with active fuse element Sealant rings: thermally stabilized adhesive Voltage loss: < 0.002 V Connection resistance: < 0.004 Ohm Insulation resistance: > 109 Ohm Assembly temperature: 210°C Thermal resistance: -60°C - +130°C Break-down voltage: > 600 V

USAGE

Assembly of car radios and alarm systems, assembly of tow hooks, repair of groups of wires, repair of pumps, repair of home appliances, lighting, neons, adverts, land, water and air transportation, industrial machines, road construction equipment, equipment for earth works, electric installations, power tools, telecommunication, agriculture, gardening, etc.

> Type electric electric

electric

electric

CLASSIFICATION

Article code	Name	Packaging
TUX100	PRO TOPFLUX SOLDER SHRINK green	50/100/200
TUX200	PRO TOPFLUX SOLDER SHRINK red	50/100/200
TUX300	PRO TOPFLUX SOLDER SHRINK blue	50/100/200
TUX300	PRO TOPFLUX SOLDER SHRINK blue	50/100/200
TUX400	PRO TOPFLUX SOLDER SHRINK yellow	50/100/200

TTP POLSKA - Top Technical Products Autonomic Group

www.ttppolska.pl