



## SUPER LUBE DURA-SLIP

DSL



### CAUTION

All information, including illustrations, are reliable. However, the users should evaluate the usability of each product for a given application. TTP Polska Sp. z o.o. does not guarantee the accuracy of all information and does not accept responsibility for how the products are used. The liabilities of TTP Polska Sp. z o.o. are limited solely to the standard terms and conditions of sale of the product and in no case whatsoever does TTP Polska Sp. z o.o. bear any responsibility for accidental or indirect damages resulting in the sale, use and improper use of the product.

## GENERAL INFORMATION

**SUPER LUBE DURA-SLIP** is a clear and transparent lubricant based on high quality mineral oils and PTFE (polytetrafluoroethylene) microspheres that work as a well adhering and filling balls in rolling bearing. **SUPER LUBE DURA-SLIP** is characterised by the lowest friction coefficient among all solid lubricants available on the market. **SUPER LUBE DURA-SLIP** provides for professional and unique lubrication at high (250°C) and low (-50°C) temperatures. **SUPER LUBE DURA-SLIP** does not dry out, melt, freeze, is resistant to water, is not subject to leaching, nor is it absorbable. **SUPER LUBE DURA-SLIP** is neutral, resistant to corrosion and features protective properties. **SUPER LUBE DURA-SLIP** is suitable both for large loads, as well as precision mechanisms. **SUPER LUBE DURA-SLIP** features a neutral pH and thus does not damage plastics, metals nor rubber.

## TECHNICAL DATA

Content: high quality mineral oil and PTFE molecules (5 microns).  
Additives: increasing adherence, anti-corrosiveness and water resistance.  
Viscosity: lightly thixotropic.  
Colour: colourless / whitish (transparent).  
Chemical resistance: resistant to salt, aggressive fumes, maritime air and influences of environmental factors, resistant to weak acids and bases.  
Application temperature: -50°C – +250°C.  
pH: neutral.

## USAGE

**INDUSTRY:** for effective, long-lasting and economical lubrication of all moving parts in: roller and rail feeders, electric pumps, ropes, toothed gears and chains, toothed pumps, submerged pumps (axle), bearings (rollers, balls), hoisting mechanisms, lifts, rollers, pneumatic hammers, lathe and milling machines, lawn mowers, precision instruments, textile machines, extruding and striking machines, sawing machines, shakers and sifters of aggregates and sand, thickeners, sunroofs, spindles, concrete mixers, valves, locks, axles, firearms, power tools, machines in timber, metal, and plastics industry, print works, mining, gardening, aviation, etc.

**AUTOMOTIVE INDUSTRY:** cars, motorcycles, bicycles, agricultural machines, water transport, land transport: lubrication of open chains, guidings and hinges, windows and door mechanisms, seat guidings, antennas, locks, pneumatic devices, earth works machines, hoists, moving and blocking elements of rockers, etc.

**SUPER LUBE DURA-SLIP** is perfectly suited for the lubrication of mating parts, made of metal and plastics, or plastics/metal combination.

## CLASSIFICATION

Article code	Name	Packaging	Type
DSL	SUPER LUBE DURA-SLIP	aerosol 400 ml	lubricants

TTP POLSKA - Top Technical Products Autonomic Group

[www.tppolska.pl](http://www.tppolska.pl)

