

TTP POLSKA Sp. z o.o.

ul. Długa 25 43-365 Wilkowice tel/fax: 33 816 04 14

e-mail: biuro@ttppolska.pl



TRANSPARENT HIGH TAPE

THT

TRANSPARENT HIGH tape ULTRA STRONG ADHESIVE AVAILABLE IN METERS Ultra strong acrylic adhesive in a roll — high adhesion strength High thermal and UV radiation resistance Resistant to chemicals and insoluble Establishes adhesive bonding between smooth and porous surfaces Easy and safe to use Available in widths: 12 and 19 mm, 33 m rolls

CAUTION

All information, including illustrations, are reliable. However, the users should evaluate the usability of each product for a given application. TTP Polska Sp. z o.o. does not guarantee the accuracy of all information and does not accept responsibility for how the products are used. The liabilities of TTP Polska Sp. z o.o. are limited solely to the standard terms and conditions of sale of the product and in no case whatsoever does TTP Polska Sp. z o.o. bear any responsibility for accidental or indirect damages resulting in the sale, use and improper use of the product.

GENERAL INFORMATION

TRANSPARENT HIGH TAPE is especially designed for establishing durable adhesive bonding. May be used both indoors and outdoors. TRANSPARENT HIGH TAPE is applicable for the adhesive bonding of many materials, e.g.: metals, glass, wood, various types of plastics and their combinations. TRANSPARENT HIGH TAPE features ultra strong adhesion and very high shearing resistance and tearing strength. It is resistant to internal tensioning. The tape is fully resistant to water, atmospheric conditions, temperatures, UV radiation and ageing. TRANSPARENT HIGH TAPE is the strongest material for double-sided adhesive bonding.

TECHNICAL DATA

Adhesive: 100% acrylic

Coating: transparent polyethylene

Colour: transparent

Thickness of adhesive layer: 1.0 mm

Sensitivity to pressing: bonds under pressure Thermal resistance: -40°C - +120°C

Solvent resistance: insoluble (resistant)

UV resistance: good Tightness: very good Specific gravity: 850 kg/m³ Shearing resistance: 67 N/cm² Dynamic breaking force: 4,900 g/cm

Shelf life: 24 months, store in dry, cool place, protect from freezing

temperatures.

LISAGE

TRANSPARENT HIGH TAPE is used in the advertising, automotive, furniture, electronic industries and others besides. It is used for the installation of showers, production of glass show-cases, fixing side car strips, spoilers, floor strips, etc. Adhesive bonding of glass products, manufacturing; consumer electronics, LCD, home appliances, connection of wall panes, connection of polycarbonate elements, fixing of type plates, etc.

CLASSIFICATION

Article code	Name	Packaging	Type
THT12	TRANSPARENT HIGH TAPE12	33 m/12 mm roll	tapes
THT19	TRANSPARENT HIGH TAPE19	33 m/19 mm roll	tapes

TTP POLSKA - Top Technical Products Autonomic Group



