



SUPER MULTI SPRAY

SMS



GENERAL INFORMATION

SUPER MULTI SPRAY acts fast and efficiently in contact with rust, tar, greases and water. **SUPER MULTI SPRAY** saves time, combining penetrating, lubricating, protection, cleaning, anti-corrosive and humidity repellent features. Additionally, it generates a cold shrinkage effect, which enables the instant disconnection of corroded connections. **SUPER MULTI SPRAY** does not contain silicone and may be safely used on plastics, varnished, etc. surfaces.

TECHNICAL DATA

Water solubility: insoluble
Density at 20°C: 0.811
Odour: distinctive
Pressure (bar): 8.53
Boiling point: 187–300°C
Relative density at 20°C: 0.81 g
Thermal resistance: -80°C – +190°C
Viscosity at 20°C: 1 mPa.s
Kinematic viscosity at 20°C: 1 mPa.s
Mineral oil based product.

USAGE

SUPER MULTI SPRAY is a highly versatile product. May be used in all industries for: loosening of jammed bolts, pins, nuts, connectors, hinges and pipe connections; removing humidity from ignition contacts and electrical wires and their protection; lubrication and cleaning of brake connections, ropes and chains; protection of metal surfaces against oxidation and corrosion.

CLASSIFICATION

Article code	Name	Packaging	Type
SMS	SUPER MULTI SPRAY	aerosol 400 ml	lubricants

CAUTION

All information, including illustrations, are reliable. However, the users should evaluate the usability of each product for a given application. TTP Polska Sp. z o.o. does not guarantee the accuracy of all information and does not accept responsibility for how the products are used. The liabilities of TTP Polska Sp. z o.o. are limited solely to the standard terms and conditions of sale of the product and in no case whatsoever does TTP Polska Sp. z o.o. bear any responsibility for accidental or indirect damages resulting in the sale, use and improper use of the product.

TTP POLSKA - Top Technical Products Autonomic Group

www.tppolska.pl

